



intertape polymer group®



**DUCT TAPE**  
PRODUCT GUIDE

# CLOTH/DUCT TAPES



Intertape Polymer Group offers a full range of cloth tape to satisfy even the most demanding requirements and industry standards. From Utility Grade to HVAC, all Intertape® brand Tapes are manufactured with high grade raw materials and held to the highest quality standards.

## PREMIUM GRADE

		Tensile		Adhesion		Thickness		Elongation %
		lb/in	N/25mm	oz/in	N/25mm	mils	mm	
<b>AC50</b>	Silver, black, olive drab; provides excellent moisture barrier; for use when a significant level of tensile and tear strength are required; meets ASTM D5486 Type 1	40.0	175.1	50.0	13.7	14.0	0.36	14.0

## MEDIUM GRADE

<b>AC36</b>	The general contractors duct tape of choice – silver, black; aggressive adhesive for high performance applications	20.0	87.5	54.0	14.8	11.0	0.28	18.0
<b>AC43†</b>	Silver; designed to meet the needs of the general contractor; aggressive natural rubber adhesive at an economical price; tested in accordance with UL723	28.0	122.0	54.0	14.8	12.0	0.30	20.0

## GENERAL GRADE

<b>AC20</b>	Available in several colors; economic all-purpose duct tape for home and office use	19.0	83.2	54.0	14.8	9.0	0.23	18.0
<b>AC30</b>	The maintenance shop duct tape – silver, red, black; ideal for shop floor applications from machine repair to leak sealing	20.0	87.5	54.0	14.8	10.0	0.25	18.0

## UTILITY GRADE

<b>AC6</b>	Silver; conformable to irregular surfaces; aggressive natural rubber adhesive; good for packaging, wrapping, sealing, binding, bundling and general maintenance	15.0	65.7	42.0	11.5	6.0	0.152	25.0
<b>AC10</b>	Ideal for wrapping, sealing and general use; conforms to irregular shapes	18.0	78.8	44.0	12.0	7.5	0.19	18.0
<b>AC15</b>	Silver, black; ideal for retail and non-critical applications	18.0	78.8	54.0	14.8	8.0	0.20	18.0

## HVAC

<b>AC45†</b>	Silver, red, black; for use in HVAC and abatement applications	25.0	109.5	50.0	13.7	12.0	0.31	18.0
<b>AC49†</b>	For use in HVAC applications where UV resistance and metallized look is preferred; ideal for flexible duct	24.0	105.1	48.0	13.1	11.0	0.28	18.0
<b>AC57</b>	Silver and black; premier grade; conforms to all UL181B requirements; designed for the professional HVAC contractor	40.0 MD 27.0 CD	175.1 MD 116.5 CD	63.0	17.2	16.0	0.41	14.0
<b>AC698</b>	Clear, black, metallized; BOPP film backed; UL181B-FX rated; designed for seaming, closing and repairing flexible duct; temperature resistant to 210°F/99°C	21.0	92.0	42.0	11.5	2.7	0.07	130.0

†Tested in accordance with UL723; Meets HUD, BOCA and LA County Codes





**CORPORATE PROFILE**

Intertape Polymer Group Inc. (IPG) is an acknowledged leader in the packaging industry. Leveraging its advanced manufacturing and technologies, extensive research and development capabilities and a comprehensive strategic acquisition program, the company believes it has assembled the broadest and deepest range of products in the industry.

IPG is widely recognized for its development and manufacture of specialized polyolefin, plastic and paper-based packaging products, as well as complementary packaging systems for industrial and retail use. Additionally, IPG is a woven and flexible intermediate bulk container (FIBC) manufacturer. Its performance products, including tapes and cloths, are designed for demanding aerospace, automotive and industrial applications and are sold to a broad range of industry/specialty distributors, retail stores and large end-users in diverse industries.

